



COUDES PVC M1 - PE – PP – PPs – 90° - RAYON 1 D. (60° et 75° en série injec-

PAR SECTEURS



Coefficient de perte de charge = 0.25

COUDES 90°			
Références	Ø	l (mm)	Epaisseur (mm)
VA-COUDE9050	50	25	1,8
VA-COUDE9063	63	25	1,8
VA-COUDE9075	75	40	1,8
VA-COUDE9090	90	40	1,8
VA-COUDE90110	110	50	1,8
VA-COUDE90125	125	40	1,8
VA-COUDE90140	140	40	1,8
VA-COUDE90160	160	50	1,8
VA-COUDE90180	180	40	1,8
VA-COUDE90200	200	50	2,5
VA-COUDE90225	225	40	1,8
VA-COUDE90250	250	50	3,0
VA-COUDE90280	280	50	2,3
VA-COUDE90315	315	50	3,0
VA-COUDE90355	355	60	3,0
VA-COUDE90400	400	50	4,0
VA-COUDE90450	450	80	3,0
VA-COUDE90500	500	80	4,0
VA-COUDE90560	560	-	-
VA-COUDE90600	600	80	4,0
VA-COUDE90630	630	70	-
VA-COUDE90700	700	90	8,0
VA-COUDE90800	800	90	8,0
VA-COUDE90900	900	100	8,0
VA-COUDE901000	1000	100	8,0